

First Named Inventor: Thomas W. BAKKER

Application No.:

-3-

IN THE CLAIMS

Please amend claims 1-25 (marked up version attached in Appendix), such that pending claims 1-25 are as follows:

92
Sub 17
~~1.(Amended) A method for axially moving a tube in a borehole in the ground, wherein the tube is moved simultaneously along and about its axis and wherein a drill is used of which the rate of material removal is independent of the direction or speed of rotation of the tube about its axis, and wherein a drive mechanism for the drill is connected to the ground and is rotated jointly with the tube characterized in that the tube is moved about its axis in a series of alternating, angularly opposite, rotating movements within a limited angular range of rotation, the angular range comprising at least one full rotation of 360°.~~

2.(Amended) A method according to claim 1, characterized in that the limited angular range of rotation is preselected to comprise less than 1800°, preferably less than 1080°, in particular less than 720°.

3.(Amended) A method according to claim 1, characterized in that the time needed to complete two consecutive, alternating angularly opposite rotating movements is at least 10 s, preferably at least 20 s.

4.(Amended) A method according to claim 1, characterized in that the frequency of alternating angularly opposite rotating movements is such that an oscillation is generated that corresponds to the base or higher order natural frequency of the tube.

5.(Amended) A method according to claim 1, wherein a series of alternating, angularly opposite, rotating movements within the pre-selected angular range of rotation is preceded and/or succeeded by a non-oscillating, continuous rotating movement about its axis.

First Named Inventor: Thomas W. BAKKER

Application No.:

-4-

Sub 1
6. (Amended) A method according to claim 1, characterized in that said tube is composed by connecting successive tube parts rotationally rigid end-to-end.

7. (Amended) A method according to claim 6, characterized in that tube parts are connected end-to-end by welding.

8. (Amended) A method according to claim 6, characterized in that said tube parts are connected while axially inserting the tube into the borehole.

012
9. (Amended) A method according to claim 1, characterized in that the tube is axially moved into the borehole in the ground to form a casing for a borehole.

10. (Amended) A method according to claim 9, wherein the tube is inserted while a borehole is being drilled by a drill.

11. (Amended) A method according to claim 1, characterized in that the pre-selected angular range of rotation includes less than 360°, preferably less than 180° to remove ground in a circular segment at the tube end, such that, when the tube is axially advanced into the borehole, a tip of the tube is advanced along a curved path.

12. (Amended) A method according to claim 1, characterized in that the torque exerted on the tube at the surface is measured while performing angularly symmetrical opposite, rotating movements within the pre-selected angular range to determine a mid-point of lower torque values.

13. (Amended) A method according to claim 1, characterized in that relative angular orientation of tube sections axially spaced apart is monitored.

First Named Inventor: Thomas W. BAKKER

Application No.:

-5-

Subcl 14. (Amended) A method according to claim 13, characterized in that said monitoring includes observing an axial line provided on the outside of the tube.

15. (Amended) A method according to claim 13, characterized in that said monitoring includes detecting angular orientations of axially spaced magnetic markings on the outside of the tube.

16. (Amended) A method according to claim 15, characterized in that said series of alternating, angularly opposite, rotating movements have an azimuth at the tube tip, said azimuth at the tube tip being controlled in response to the orientation of the tube in the area of the ground surface.

92 17. (Amended) A method according to claim 16, characterized in that an alternating torque having an azimuth is exerted to said tube, said azimuth at the tube tip being further controlled in response to the orientation of the tube in the area of the ground surface when said azimuth of said torque occurs.

18. (Amended) A method according to claim 1, characterized in that pumping of mud is continued while a connection with a next tube section is being made via a hose and packer combination which sealingly connects to the tube section in the hole.

19. (Amended) A device for axially moving a tube in a borehole in the ground, comprising means for moving the tube along and about its axis and connections for connecting the ground to a drive mechanism for a drill carried on a bottom most part of the tube and rotating jointly with the tube, characterized in that the means for moving the tube about its axis comprises a rotational drive that is arranged to drive the tube to rotate about its axis in at least one full rotation and that is operatively coupled to control means for controlling the drive to perform alternating, angularly opposite, rotating movements within a limited angular range of rotation, the angular range comprising at least one full rotation of 360°.

First Named Inventor: Thomas W. BAKKER

Application No.:

-6-

SubC17
~~20.(Amended) A device according to claim 19, characterized in that the limited angular range of rotation is preselected to comprise less than 1800°, preferably less than 1080°, in particular less than 720°.~~

21.(Amended) A device according to claim 19, characterized in that the rotational drive and the control means are further configured to selectively control the drive to perform a continuous, non-alternating, rotating movement.

Q2
22.(Amended) A device according to claim 19, characterized in that it comprises a welding apparatus for welding tube segments end-to-end to form a composed tube, which welding apparatus is arranged to rotate substantially jointly with the tube to be moved in the borehole.

23.(Amended) A device according to claim 22, characterized in that it is provided with means for surface treatment of the inner and/or outer surface of the tube to be inserted.

24.(Amended) A device according to claim 22, characterized in that it is provided with means for aligning and positioning tube ends to be connected.

25.(Amended) A packer for sealing a tube and arranged to rotate substantially jointly therewith, comprising connecting means for connecting to a fluid or energy supply, characterized in that said connecting means are arranged to fixedly couple the packer to a flexible fluid or energy supply extending from the fluid source.